

# C2

## HIGH PERFORMANCE CONE CRUSHER

The McCloskey™ C2 Cone Crusher is the ideal portable secondary crushing solution for the operator requiring performance rates up to 300TPH. It is designed for optimum versatility in crushing spreads, with easy conversion from the finest to the coarsest cavity, adjustable speed to produce a higher percentage of on-spec product, and fewer crushing stages, lowering cost and saving energy.

The C2 distinguishes itself with full-level features like an antispin system, load and material level monitoring, fully hydraulic push button Closed Side Setting (CSS) adjust and full hydraulic relief system.



### CRUSHING CHAMBER

Built to be reliable in the toughest operating conditions, the cone on the C2 produces 3/8" to a 1 1/2" product.



### FEEDER

Steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone

### MAGNET

Reversible magnet enables material separation from the source material.



### MATERIAL FLOW

Large gap between crusher discharge and the main conveyor feedboot prevents bottlenecks.

Engine	350 Hp (261 kW) - 360 Hp (268 kW)
Cone	MC200
Feed Opening	38" (914mm)
Feeder Belt Width	42" (1050mm)
Hopper Volume	6.2m <sup>3</sup> (8.1yd <sup>3</sup> )
Crusher Drive	Direct Drive
CSS Adjustment	Hydraulic
Transport Height	11' - 1.8" (3.4m)
Transport Length	54' - 4.7" (16.6m)
Transport Width	9' - 1.4" (2.80m)
Weight	103,617 lb (47,000kg) (est.)
Stockpile Height - Main Conveyor	14' - 0.5" (4281mm)
Main Conveyor Belt Width	48" (1200mm)