

I54 HIGH PERFORMANCE IMPACT CRUSHER

A leader in the sub-50 tonne class, the McCloskey I54 Impactor brings high quality and high production capacity to mobile impactor applications.

The I54 is built around a 47" x 53" four bar impactor chamber with a 37" x 53.5" feed opening. An independently vibrating 53.3" x 69" double-deck pre-screen removes the majority of the fines in advance of the crushing chamber, increasing capacity and reducing wear.

Available with a roll-in bogie, the I54 is easily transported and has a minimal setup time, maximizing production time.




Control Panel
User-friendly waterproof and dust-proof control panel. Allows monitoring of pressures, fluid levels, and fuel consumption. Provides push button control of jaw, track and feeder functions.




Conveyor
Extended 48" main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically and is easily removable for maintenance.



Power Unit
CAT C13 430hp (320kW) engine with roomy engine bay for maintenance. Innovative hydraulic system provides significant improvements in fuel economy.



Feeder
Folding Hardox® hopper mounted over vibrating feeder with integral pre-screen. Feeder rate can be regulated manually or automatically by the load-sensing jaw.



Crusher Pre-Screen
Crusher pre-screen maximizes crusher efficiency and creates additional product.

I54

Engine: 430 hp (320 kw) CAT C13 Diesel
 Transport Height: 11' 9.6" (3.6m)
 Transport Length: 53' 7" (16.33m)
 Transport Width: 9' 10" (3m)
 Stockpile Height: 4210mm (13' - 10")
 Weight: 106,260 lbs (48,200 kg) inc. magnet

I54
HIGH PERFORMANCE
IMPACT CRUSHER



877-217-4474
 36 Hazleton St., Ashley PA 18706
www.commonwalthequipment.com