

# Eggersmann F 25

High-Torque Dual-Shaft Shredder



North America Inc.

sales@eggersmann-na.com

www.eggersmann-na.com

Shredding a wide range of applications, with high production and excellent uptime, and all this on start with a small footprint - that's what the Eggersmann F 25 stands for.

## Product Highlights

- › Individually adjustable shredding programs
- › Asynchronously running shafts for perfect shredding results and continuous shredding
- › Hydraulic tipping hopper
- › Optional breaker bars for product sizing

## Applications

- › Waste Wood
- › Green Waste
- › Solar Panels
- › Roots
- › Stumps
- › Concrete
- › Asphalt
- › Municipal Solid Waste (MSW)
- › Construction and Demolition Waste (C&D)
- › Commercial Waste
- › Electronic Waste
- › Glass
- › Shingles
- › Windmill blades
- › Mattresses

## Product Features

### Perfect Feeding

- › Hopper can be raised and lowered
- › Easy and fast feeding by wheel loader or excavator
- › Operation via radio remote control

### Individually Adjustable Shafts

- › Individually adjustable direction and speed of rotation
- › Self-cleaning mechanism
- › Ideal for material with risk of wrapping

### Multifunctional Rotor Tools

- › Shafts with versatile rotor tools
- › Able to handle a wide range of applications

### Intuitive Control

- › Individual programs for best shredding results
- › Option to create custom settings
- › Eggersmann One-Logic interface and radio remote control

### Overbelt Magnet

- › The height-adjustable magnet can discharge metals to both sides

### Easy Maintenance

- › Large maintenance doors allow easy access to the engine compartment from ground level

## Options

### Dust Suppression Device

- › Ecospray dust suppression to reduce dust emissions

### Hopper Extension

- › Hopper extension for more volume
- › Can be combined with automatic tipping hopper function
- › Enables even faster and easier material infeed

### Specific Product Sizing

- › Breaker bars for product sizing: 4", 6", 12", 20"
- › Tool-free breaker bar change
- › Hydraulic mounting and locking for quick change in less than 10 minutes



# Eggersmann F 25


High-Torque Dual-Shaft Shredder



North America Inc.

sales@eggersmann-na.com

www.eggersmann-na.com

	Tracks	Hook Lift	Hook Lift 	Stationary
	diesel-hydraulic	diesel-hydraulic	electro-hydraulic	electro-hydraulic
Power (kW/hp)	186/252	186/252	132	132
Production up to (tph)	40	40	40	40
Weight (lbs)	43,000	33,000	33,000	33,000
Rotor speed (rpm)	5 - 28	5 - 28	5 - 28	5 - 28

## Working Dimensions

Length (ft.)	34.68	34.68	34.68	20.42
Width (ft.)	8.37	7.71	7.71	9.58
Feeding height (ft.)	9.17	8.27	8.27	9.63
Discharge height (ft.)	13.09	12.01	12.01	

## Transport Dimensions

Length (ft.)	27.03	27.01	27.01	
Height (ft.)	9.35	8.27	8.27	
Width (ft.)	8.04	7.71	7.71	



Easy Maintenance



Overband Magnet



Intuitive Control



Dust Suppression