



# **High Performance Cone Crusher**

The McCloskey™ C2 Cone Crusher is the ideal portable secondary crushing solution for the operator requiring performance rates up to 300TPH. It is designed for optimum versatility in crushing spreads, with easy conversion from the finest to the coarsest cavity, adjustable speed to produce a higher percentage of on-spec product, and fewer crushing stages, lowering cost and saving energy.

Both the C2 & C2R have full-level features such as load and material level monitoring, full hydraulic push button Closed Side Setting (CSS) adjust and a full hydraulic relief system.

## **Features**

- MC200 Cone
- Tracked
- Integrated hopper with folding rear door
- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor
- Fast setup time

- Open chassis design for ease of maintenance
- High speed, high throw 200Hp cone



### **Crushing Chamber**

Built to be reliable in the toughest operating conditions, the cone on the C2 has a minimum setting of 13mm (0.5") and a maximum feed



#### **Material Flow**

Large clearance between crusher discharge and the main conveyor feedboot prevents bottlenecking.

## Long Stroke (77mm)

Feeder

Heavy Duty steel hopper with adjustable feed rate via control

panel, remote control or fully automatic regulation with

feedback from the cone

Excellent productivity through long stroke and high speed in terms of capacity, reduction and end product shape.

## SPECIFICATION DATA

## **Dimensions and Capacities**

360 Hp (268 kW) Engine

MC200 Cone

38" (914mm) Feed Opening

42" (1050mm) Feeder Belt Width

5m<sup>3</sup> (6.5yd<sup>3</sup>) Hopper Volume

**Direct Drive** Crusher Drive

Hydraulic CSS Adjustment

11' - 1.8" (3.4m) Transport Height

54' - 4.7" (16.6m) Transport Length

9' - 1.4" (2.8m) **Transport Width** 

Weight 106,770 lb (40,470kg)

(est.)

Stockpile Height

Main Conveyor

Main Conveyor Belt Width

48" (1200mm)

14' - 0.5" (4281mm)

©Copyright 2020 McCloskey International. All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.