



Smarter Washing Solutions

AGGST RM

Modular Scrubbing Range

TECHNICAL DATA

LOGWASHER PRE SCREEN

- Single and double deck pre screen option to remove sand prior to logwasher
- Isoslated spraybars
- Rubber lined catchbox and chute for wear and noise reduction.

TRASH SCREEN

- Linear vibrating screen for the removal of lights and trash contaminants
- Rubber lined catchbox and chutes for wear and noise reduction

PIPEWORK

- Pre-plumbed at factory
- Rubber lined pipework at wear points

LOG WASHER

• Twin shaft log washer

MWS"

- Multiple paddle configurations
- Access doors to allow ease of maintenance to logwasher hull

WALKWAYS

- Full access to all areas of machine
- Galvanised walkways as standard
- 2.5ft (762mm) wide walkways



- Multiple screen options producing up to 3 aggregates
- Isolated spraybars
- Rubber lined catchbox and chute for wear and noise reduction

METRIC	8	15	XL	
Capacity	60-80 MTPH	80-150 MTPH	150-200 MTPH	
Power Requirement	51kW	59kW	75kW	
Water Requirement	80m³/hr	100m³/hr	100m³/hr	
Height	7.2m	8m	8m	
Width	5.1m	5.1m	5.1m	
Length	8m	10m	10m	

IMPEDIAL		T.	I
IMPERIAL	8	15	XL
Capacity	66-86 STPH	88-165 STPH	165-220 STPH
Power Requirement	68HP	79HP	100HP
Water Requirement	350 USgpm	440 USgpm	440 USgpm
Height	24'	26'	26'
Width	17'	17'	17'
Length	26'	32'	32'

2

Headquarters

47 Moor Road, Coalisland, Co. Tyrone, BT71 4QB, N. Ireland

+44 (0) 28 87 740 926

F +44 (0) 28 87 747 242

sales@mwswashing.com

W

A Metso:Outotec Business

mwswashing.com

Linked in. You Tube Smarter Washing Solutions